


atelier sedap / LIGHTING

197 Design Atelier Sedap

Corniche is a high strength plaster profile for indirect T5 fluorescent or linear LED lighting.



Weight

11.7 Kg

Orientation



FINISHES

Natural plaster finish

AA

LIGHT SOURCES

| REFERENCE | DESCRIPTION | LENGTH |
|-----------|--|--------|
| 197 | High strength plaster profile LEDs strips or fluo T5 as an option | 2,50 M |

CORNICHE / LED EQUIPEMENT

| REFERENCE | DESCRIPTION |
|----------------|--|
| 8129 .LDT | 5 ml High Power LED strip, warm white (2700 °K) - 120 LEDs /m, 5cm divisible Consumption 19.2 W per meter - 24V - 2000 lumens per meter |
| 8130-1 .LDT | 5 ml High Power LED strip, warm white (3000 °K) - 120 LEDs /m, 5cm divisible Consumption 19.2 W per meter - 24V - 2000 lumens per meter |
| 8099 .LDT | 5 ml LED strip, warm white (2700 °K) - 60 LEDs /meter, 10cm divisible Consumption 15 W per meter - 24V - 1080 lumens per meter |
| 8100 .LDT | 5 ml LED strip, warm white (3000 °K) - 60 LEDs /meter, 10cm divisible Consumption 15 W per meter - 24V - 1080 lumens per meter |
| 8102 .LDT | 5 ml RGB LED strip - 60 LEDs /meter, 10cm divisible Consumption 15 W per meter - 24V |
| 5179 | Aluminium heatsink section (20 x 6 mm), length 1 meter |
| 011070025 | High frequency presence sensor (more info) |

Find here the power supplies, drivers and RGB kits.

CORNICHE / FLUO T5 EQUIPEMENT

| REFERENCE | DESCRIPTION |
|-----------|---|
| 5170 | T5 fluorescent equipment, with electronic ballast and aluminium reflector (supplied excluding lamps) P. 24 W 580 mm - Option: dimmable ballast (1-10V) |
| 5171 | T5 fluorescent equipment, with electronic ballast and aluminium reflector (supplied excluding lamps) P. 21-39 W Multiwatt 880 mm - Option: dimmable ballast (1-10V or DALI) |
| 5172 | T5 fluorescent equipment, with electronic ballast and aluminium reflector (supplied excluding lamps) P. 28-54 W Multiwatt 1180 mm - Option: dimmable ballast (1-10V or DALI) |
| 011070025 | High frequency presence sensor (more info) |